


Quick Start Guide



The following is a brief description on how to setup and use the Model 530 Chocolate Temper Meter.

Should you have any questions or encounter any problems please contact us at:

TRICOR Systems, Inc.
1650 Todd Farm Drive
Elgin, IL 60123
1-847-742-5542
www.tricor-systems.com

Power Up Sequence

The image to the left is displayed during power up initialization, along with progress bars showing:

- Initializing System ... during this sequence the unit performs a self-test, initializes parameter settings and electronic circuits
- Searching Stored Results ... during this sequence the unit verifies the stored run memory area and initializes stored run search parameters

The Self-Test result screen is displayed next

When the self-test passes, the screen is visible for approx 2 seconds, then continues

- no operator action is required
- if self-test fails the screen will remain displayed, showing which test(s) failed
- record the failed test(s) and contact TRICOR
- press Continue

The next screen displays the cooler and heater temperature readings and set points while the unit waits for the cooler and heater to reach their set points

Performing a Test Run

Figure 1 ... Operator Action Required - ID Entry

```

Model 530 Chocolate Temper Meter
09/19/09 11:32am

Last Run: CTU= 6.5 Slope=+ 0.67

Enter ID(s) before inserting sample

Prod ID      Oper ID      Line ID      Plnt ID
530          123          Off          Off

Oper ID =           

Press Enter to accept new (or curr) val
Press Continue to accept current value

```

Test Run sequence ...

- wait for unit temperature stabilization
- enter desired ID's (if any ID enable = On) (Fig 1)
- wait for "Ready For Sample" message (Fig 2)
- remove sample cup from front of unit, fill cup such that chocolate is just below lip and above the fluted area
- lift sample lid, insert filled cup into well, slide knob right, close lid
- test run begins ...
 - during a test run data is displayed the same as the stored runs display (Fig 8 or Fig 9) except if in graph mode the current sample time, temp and slope is displayed just below the ID's while the temp is plotted on the graph
- wait for test run completion
- test data printed to internal printer
- slide knob left, lift lid, remove sample cup, close lid
- if applicable, test data will be printed on the external printer
 - if enabled the statistical graph is displayed

Figure 2 ... Unit Ready for Test Run

```

Model 530 Chocolate Temper Meter
09/19/09 11:32am

Last Run: CTU= 6.5 Slope=+ 0.67

Ready For Sample

Prod ID      Oper ID      Line ID      Print ID
530          Off          Off          Off

```

To abort a test run, lift sample lid, remove sample, then close the lid.

Press the "Status" key when either of these screens (Fig 1 or Fig 2) is displayed to access the SYSTEM STATUS screens which are used to view stored runs, statistics or parameter settings and to access menus for configuration programming

Navigating Through Status and Menu Screens

Figure 3 ... Sample Status Screen

```

Model 530 Chocolate Temper Meter
09/19/09 11:32am

SYSTEM STATUS

Stored Runs      Prod ID Enab      Auto
Statistics       Product ID        530
→ ID Settings    Oper ID Enab      Off
Test Parameters  Operator ID        99999
Unit Parameters  Line ID Enab      Off
Display Setup    Line ID            99999
Print Setup      Plnt ID Enab      Off
Graph Setup      Plant ID            99999
System Info      Last Test ID       486

Press Enter to view Menu
Scroll Up/Down to view Settings
Press Cancel to return to Main screen

```

- press Scroll Up, Scroll Down keys to navigate through status group screens (Fig 3) and menu screens (Fig 4)
- current parameter values are displayed on the right side of the screen
- when the desired Status group name is highlighted, press Enter to access menus and submenus
- when the desired menu item is highlighted, press applicable keys (see Figs 5, 6) to change value or press Enter to change numeric values
- press Print (from any SYSTEM STATUS screen) to print the unit's status information on the internal printer
- for all screens the bottom 3 lines of the display describe which keys to press for navigation

Figure 4 ... Sample Menu Screen

```

Model 530 Chocolate Temper Meter
09/19/09 11:32am

Set ID Parameters

>Prod ID Enable Auto
Preset Product ID 530
Oper ID Enable Off
Preset Operator ID 99999
Line ID Enable Off
Preset Line ID 99999
Plant ID Enable Off
Preset Plant ID 99999

Enter= decr val Status= incr val
Pscroll Up/Down for menu item selection
Press Cancel to return to Status screen

```


Parameter Descriptions and Uses

Status Group	Parameter	Description
Stored Runs	-	used to view and print stored runs
Statistics	-	used to view and print statistical analysis of stored runs for a selected Product ID
	Auto Disp Stat Graph	On = unit will display statistical graph at the end of the test run (after any printing is completed)
	CTU Low Limit	used on the statistical graph display to highlight a user specified range for acceptable test run results
	CTU High Limit	
	Slope Low Limit	
ID Settings	Slope High Limit	
	ID Enables	Off = ID not used (ref Fig 8) On = operator action required prior to test run (must accept current value or enter a new value) Auto = automatically uses preset ID value for a run
	ID Presets	valid range is 1 to 99999
	Last Test ID	not user accessible, this is a sequential run number the unit assigns to each test run
Test Parameters	Degrees	temperature unit of measurement - °C or °F
	Runtime	valid range is 3:00 to 9:55 minutes, in 30 second incr's
	CTU Cutoff	If the 2nd inflection point occurs below this setting the test result will be No Inflection
	Result string format	CTU / Slope 2 ... CTU result and the slope at the 2nd inflection point (ref Fig 8) S2 / T1 / T2 ... the slope at the 2nd infl pt, the temps at the 1st and 2nd inflection points (ref Fig 9)
Unit Parameters	Date/Time	sets unit clock, sets the time format (12 or 24hr) and the date format (dd/mm/yy or mm/dd/yy)
	CTU Offset	this value is added to the calculated CTU result which allows users to obtain CTU results that correlate with previously obtained test data or which are more familiar to the user

Status Group	Parameter	Description
Unit Parameters	Line Frequency	programs A/D filter circuit for power line frequency - 50 hz or 60 hz
	Alarm Enable * (end of run and self-test alarm sound is 50 cycles of triple beeps)	On = internal beeper will sound when: - keys are pressed (short clicking sound) - at end of test run * - if self-test fails (except on power-up) *
	Cooler Ref	available with the Programmable Cooler Option; allows user to change Cooler Reference
Display Setup	Run Data Disp Format	controls how test run data (real time or stored) is displayed - as a graph (Fig 8) or a data list (Fig 9)
	Disp Infl Pts Enable	controls displaying of inflection point data
	Color Settings	sets the displayed color of various displayed items - text, background, graph and No Infl highlight
Print Setup		controls internal printer test run data format Off = test run will not be printed Short = only the header and results will be printed Shrt/Gr = the graph will also be printed Long = each 5 second sample point will be printed Long/Gr = the graph will also be printed
	Int Printout Format	
	Auto Print Ext	available with the External Print / Plot option Off = test run will not be printed On = test run data will be printed on external printer at end of run (starts when sample is removed)
Graph Setup	Set Graph Baseline	sets the baseline for the temperature axis of all graphs (display, internal and external printer)
System Info	System Readings	displays various temperature, voltage and current readings of internal electrical circuits
	Self-Test	performs system self-test
programmed through UserApp530 only	Sample Description	a string containing up to 12 characters is stored with each test run (ref Fig 9)

Changing Parameter Values

Figure 5 ... Changing fixed value settings




- two value settings
press Enter to toggle
- multi-value settings
press Status to increment
press Enter to decrement
- see lines at bottom of display for description of which key(s) to use based on the currently selected parameter

to display a Statistical Analysis graph ...

- from the SYSTEM STATUS screen navigate to the Statistics group and press Enter
- select the View Stats by Prod ID menu item and press Enter
- select the desired Prod ID and press Enter


Figure 6 ... Changing numeric settings



- press numeric keys to change value
 - press Enter to accept new value
 - press Backspace to clear last key entered
- press Cancel to exit without changing value

Statistical Data Viewing

Figure 7 ... Statistical Analysis Graph




- press Print to send statistical data results to the internal printer (the graph is not printed)
- up to 120 run results are displayed, if more are stored the latest 120 are displayed
 - all stored runs for the selected Product ID are included in the calculations, even if not displayed
 - oldest data is to the left, newest to the right. each dot represents one test run result
- Product ID's are selected through a menu that includes up to 9 ID's, if more are stored then an additional menu item is displayed to allow user entry of an ID via the keypad

5

Stored Run Viewing

Figure 8 ... Stored Run - Graph




(Result string format = CTU / Slope 2)
("-----" signifies ID enable = Off)

- * holding down any scroll key switches to fast scroll mode:
 - stored run scrolling - only the header data is displayed
 - list scrolling - only one line of time, temp, slope is displayed

to display stored run data ...

- from the SYSTEM STATUS screen navigate to the Stored Runs group and press Enter
- select the View Stored Runs menu item and press Enter
- first run displayed is last run stored (newest)
- display format graph (Fig 8) or list (Fig 9) per "Run Data Display Format" setting
- press Print
 - internal printout format per "Int Printout Format"
 - if the external printer option is present then a menu pops up to select where to print: "1 = Int 2 = Ext"
- scrolling through stored results
 - press Enter to scroll to previous run (older) *
 - press Status to scroll to next run (newer) *
 - press "+/-" to scroll to 10th prev run (older) *
 - press "3" to scroll to 10th next run (newer) *
- scrolling will automatically rollover at memory boundaries
 - if currently viewing newest and scroll "Next" past memory boundary then oldest will be displayed
 - if currently viewing oldest and scroll "Prev" past memory boundary then newest will be displayed

Figure 9 ... Stored Run - List




(Result string format = S2 / T1 / T2 and run has a Sample Description)

- scrolling through list format sample data
 - press Scroll Up/Down keys for single step scroll *
 - press "6" key to page up through list *
 - press "9" key to page down through list *

6

Figure 10 ... Printer Buttons (as viewed on unit)



- carefully pull access door lever (Fig 10, 11) until door is released from its locked position
- remove empty roll
- insert new roll, leave approx 2 cm (3/4 in) outside door (Fig 12)
- close door by carefully pressing the center of door until door locks closed (Fig 13)
- a pink stripe at edge of paper signifies end of paper roll

Changing Printer Paper Roll

Figure 11 ... Open paper access door




Figure 12 ... Insert new paper roll



Figure 13 ... Close and lock access door




Figure 14 ... Power Entry Module (rear panel)



fuse access door (remove power cord before opening)


Figure 15 ... Keypad Buttons



(hold any scroll key down for fast scroll mode)

Figure 16 ... Serial Comm Connectors (rear panel)

USB (Type B) (used with UserApp530 and TMDAS PC programs)



RS-232 (RJ-11) (used with External Print / Plot option)

7

Specifications

Dimensions	27h x 47w x 38d cm 10.5h x 16.5w x 15.0d inches
Weight	8.7kg (19 lbs)
Power Requirements	Universal AC Input range 90 to 250 vac, 50 or 60 Hz 1.7A @ 115vac (0.85A @ 230vac)
Internal Memory Storage	165 five minute runs
Sample Test Time	3 to 10 minutes (programmable)
Sample Volume	11.0 mL (0.38oz)
Sample Stabilization Time	30 sec
CTU Repeatability	± 0.5 ctu
Cooler Stability	±0.06°C (±0.1°F)
Probe Heater Temperature Accuracy	±0.6°C (±1.0°F)
Temperature Measurement Sensitivity	±0.003°C (±0.005°F)
Temperature Measurement Range	-8° to 55°C (18° to 131°F)
Ambient Operating Temperature Range	10° to 41°C (50° to 105°F)

Temper Curve Graph Scales	
Temperature axis scale	14°C (28°F) (display, printouts)
Temperature axis baseline	14° to 32°C (56° to 92°F) (display, printouts)
Time axis scale	5 min or 10 min (display) per test run (printouts)

Self-Test automatic on power up
can also be run from menu

Color TFT LCD Display 16 user selectable colors
LED backlight
320w x 234h pixels
40 characters (w) x 29 lines (h)

PC Configuration Application PC program used for
(UserApp530) configuration setup

RoHS Compliant EU Directives 2002/95/EC and 2005/618/EC


Sample cup storage tube capacity 80 cups

Supplies

Sample cups (box of 5000)	130-226
Printer Paper roll (box of 24)	321-161
Well cleaning tool	130-245

Options

Programmable Cooler Temperature	321-420
External Print / Plot (includes dot matrix printer)	321-421
Data Acquisition Application (TMDAS)	150-124



TRICOR Systems, Inc.
1650 Todd Farm Drive
Elgin, IL 60123
1-847-742-5542
www.tricor-systems.com

8

Doc Num 321-403 Rev -